


Features

- Voltage Controlled Crystal Oscillator (VCXO).
- Fundamental solution.
- Package size: 3.2×2.5×0.95 mm.
- CMOS output, output frequencies 50MHz to 200MHz.
- Excellent low phase noise and jitter.
- 3-state function available.
- Automatic mounting and reflow soldering.
- Applications: SDH, SONET, Ethernet, Base Stations, Femtocell, Satellite, etc.
- RoHS Compliant / Pb-Free.




Electrical Specifications

Item /Type	3S (SMD 3225 VCXO)
Output Type	CMOS
Output Load	15pF, or specify
Oscillation Mode	Fundamental
Supply voltage	3.3V
Frequency range	50MHz~200MHz
Frequency Stability*	±25ppm, ±50ppm, ±100ppm
Operating Temperature Range	-20~+70°C, -40~+85°C, or specify
Storage Temperature Range	-55~+125°C
Voltage Vol (Typ.) / Voh (Typ.)	0.1VDD / 0.9VDD
Rise(Tr) / Fall(Tf) Time(20%~80%)	5nS Max.
Supply Current	60mA Max.
Symmetry	45~55%
Start-up Time	10ms Max.
Absolute Pulling Range (APR)*	±50ppm Min., or specify
Nominal Control Voltage	0.5VDD
Control Voltage Range	0~VDD
Linearity	10% Max.
Phase Jitter(12KHz~20MHz)	1pS Max

* APR=(Pull Range)-(Frequency tolerance at 25°C, variation over temperature, supply voltage variation, and aging.)

Dimensions

Units:mm



PAD FUNCTION:
 1: CONTROL VOLTAGE
 2: ENABLE CONTROL or NC
 3: GND
 4: OUT
 5: NC
 6: VDD

